

Solid State Logic
O X F O R D • E N G L A N D

SSL 18 - Multi-language Safety Instructions

Industry Canada Compliance
This Class B digital apparatus complies with Canadian ICES-003.

UKCA

Important Information Inside

EN

SSL 18 - Important Safety Information
General Safety
Please read and keep this document and adhere to all warnings and instructions. This electrical equipment should not be exposed to dust, water, or other liquids.

The Eco-design requirements for Energy related products (ErP) 2009/125/EC.
The restriction of the use of certain Hazardous Substances in Electrical and Electronic Equipment Directive 2011/65/EU.

Electromagnetic Compatibility
BS EN 55032:2015, Class B. BS EN 55035:2017.

WARNING: The audio input/output ports are screened cable ports and any connections to them should be made using braid-screened cable and metal connector shells to provide a low impedance connection between the cable screen and the device.

DA
The unit can only be serviced by qualified personnel – seek immediate service if the console has been exposed to water or if it ceases to operate normally.

SSL does not accept liability for damage caused by maintenance, repair or modification by unauthorised personnel.

When using this apparatus either fix it into a standard 19" rack or place it on a secure level surface.

If the unit is rack mounted, fit all rack screws. Rack shelves are recommended.

Do not block any ventilation openings. Install in accordance with the manufacturer's instructions.

Always allow free air flow around the unit for cooling.

Ensure that no strain is placed on any cables connected to this apparatus. Ensure that all such cables are not placed where they can be stepped on, pulled or tripped over.

Power safety: This product satisfies FCC regulations when high quality shielded cables are used to connect with other equipment. Failure to use high quality shielded cables or to follow the installation instructions may cause electromagnetic interference with appliances such as radios and televisions and will void your FCC authorisation to use this product.

This equipment is supplied with mains lead however if you wish to use a mains cables of your choice refer to the following information:

Refer to the rating label on rear of the unit and always use a suitable mains cord.

The unit should ALWAYS be earthed.

Please use a compliant 60320 C13 TYPE SOCKET. When connecting to supply outlets ensure that appropriate sized conductors and plugs are used to suit local electrical requirements.

Maximum cord length should be 4.5m(15').

The cord should bear the approval mark of the country in which it is to be used.

Additionally: The appliance coupler is used as the disconnect device, ensure that it is correctly fitted to the wall outlet.

Connect directly to an AC power source that contains a protective earthing (PE) conductor.

ATTENTION! This product must always be earthed.

CAUTION! No user-serviceable parts inside. In the event of damage to the unit contact Solid State Logic. Service or repair must be done by qualified service personnel only.

This product complies with the following United Kingdom Legislation:

UK Electrical Equipment (Safety) Regulations 2016 (SI 2016/101)

UK Electromagnetic Compatibility Regulations 2016 (SI 2016/109).

The Eco-design requirements for Energy related products (ErP) 2009/125/EC.

The restriction of the use of certain Hazardous Substances in Electrical and Electronic Equipment Directive 2011/65/EU.

The unit is to be connected to a 19" rack.

Mount the unit in the rack using the correct number of screws.

Do not block any ventilation openings.

Install in accordance with the manufacturer's instructions.

Always allow free air flow around the unit for cooling.

Ensure that no strain is placed on any cables connected to this apparatus. Ensure that all such cables are not placed where they can be stepped on, pulled or tripped over.

Power safety: This product satisfies FCC regulations when high quality shielded cables are used to connect with other equipment. Failure to use high quality shielded cables or to follow the installation instructions may cause electromagnetic interference with appliances such as radios and televisions and will void your FCC authorisation to use this product.

This equipment is supplied with mains lead however if you wish to use a mains cables of your choice refer to the following information:

Refer to the rating label on rear of the unit and always use a suitable mains cord.

The unit should ALWAYS be earthed.

Please use a compliant 60320 C13 TYPE SOCKET. When connecting to supply outlets ensure that appropriate sized conductors and plugs are used to suit local electrical requirements.

Maximum cord length should be 4.5m(15').

The cord should bear the approval mark of the country in which it is to be used.

Additionally: The appliance coupler is used as the disconnect device, ensure that it is correctly fitted to the wall outlet.

Connect directly to an AC power source that contains a protective earthing (PE) conductor.

ATTENTION! This product must always be earthed.

CAUTION! No user-serviceable parts inside. In the event of damage to the unit contact Solid State Logic. Service or repair must be done by qualified service personnel only.

This product complies with the following Canadian ICES-003.

Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

The unit is to be connected to a 19" rack.

Mount the unit in the rack using the correct number of screws.

Do not block any ventilation openings.

Install in accordance with the manufacturer's instructions.

Always allow free air flow around the unit for cooling.

Ensure that no strain is placed on any cables connected to this apparatus. Ensure that all such cables are not placed where they can be stepped on, pulled or tripped over.

Power safety: This product satisfies FCC regulations when high quality shielded cables are used to connect with other equipment. Failure to use high quality shielded cables or to follow the installation instructions may cause electromagnetic interference with appliances such as radios and televisions and will void your FCC authorisation to use this product.

This equipment is supplied with mains lead however if you wish to use a mains cables of your choice refer to the following information:

Refer to the rating label on rear of the unit and always use a suitable mains cord.

The unit should ALWAYS be earthed.

Please use a compliant 60320 C13 TYPE SOCKET. When connecting to supply outlets ensure that appropriate sized conductors and plugs are used to suit local electrical requirements.

Maximum cord length should be 4.5m(15').

The cord should bear the approval mark of the country in which it is to be used.

Additionally: The appliance coupler is used as the disconnect device, ensure that it is correctly fitted to the wall outlet.

Connect directly to an AC power source that contains a protective earthing (PE) conductor.

ATTENTION! This product must always be earthed.

CAUTION! No user-serviceable parts inside. In the event of damage to the unit contact Solid State Logic. Service or repair must be done by qualified service personnel only.

This product complies with the following Canadian ICES-003.

Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

The unit is to be connected to a 19" rack.

Mount the unit in the rack using the correct number of screws.

Do not block any ventilation openings.

Install in accordance with the manufacturer's instructions.

Always allow free air flow around the unit for cooling.

Ensure that no strain is placed on any cables connected to this apparatus. Ensure that all such cables are not placed where they can be stepped on, pulled or tripped over.

Power safety: This product satisfies FCC regulations when high quality shielded cables are used to connect with other equipment. Failure to use high quality shielded cables or to follow the installation instructions may cause electromagnetic interference with appliances such as radios and televisions and will void your FCC authorisation to use this product.

This equipment is supplied with mains lead however if you wish to use a mains cables of your choice refer to the following information:

Refer to the rating label on rear of the unit and always use a suitable mains cord.

The unit should ALWAYS be earthed.

Please use a compliant 60320 C13 TYPE SOCKET. When connecting to supply outlets ensure that appropriate sized conductors and plugs are used to suit local electrical requirements.

Maximum cord length should be 4.5m(15').

The cord should bear the approval mark of the country in which it is to be used.

Additionally: The appliance coupler is used as the disconnect device, ensure that it is correctly fitted to the wall outlet.

Connect directly to an AC power source that contains a protective earthing (PE) conductor.

ATTENTION! This product must always be earthed.

CAUTION! No user-serviceable parts inside. In the event of damage to the unit contact Solid State Logic. Service or repair must be done by qualified service personnel only.

This product complies with the following Canadian ICES-003.

Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

The unit is to be connected to a 19" rack.

Mount the unit in the rack using the correct number of screws.

Do not block any ventilation openings.

Install in accordance with the manufacturer's instructions.

Always allow free air flow around the unit for cooling.

Ensure that no strain is placed on any cables connected to this apparatus. Ensure that all such cables are not placed where they can be stepped on, pulled or tripped over.

Power safety: This product satisfies FCC regulations when high quality shielded cables are used to connect with other equipment. Failure to use high quality shielded cables or to follow the installation instructions may cause electromagnetic interference with appliances such as radios and televisions and will void your FCC authorisation to use this product.

This equipment is supplied with mains lead however if you wish to use a mains cables of your choice refer to the following information:

Refer to the rating label on rear of the unit and always use a suitable mains cord.

The unit should ALWAYS be earthed.

Please use a compliant 60320 C13 TYPE SOCKET. When connecting to supply outlets ensure that appropriate sized conductors and plugs are used to suit local electrical requirements.

Maximum cord length should be 4.5m(15').

The cord should bear the approval mark of the country in which it is to be used.

Additionally: The appliance coupler is used as the disconnect device, ensure that it is correctly fitted to the wall outlet.

Connect directly to an AC power source that contains a protective earthing (PE) conductor.

ATTENTION! This product must always be earthed.

CAUTION! No user-serviceable parts inside. In the event of damage to the unit contact Solid State Logic. Service or repair must be done by qualified service personnel only.

This product complies with the following Canadian ICES-003.

Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

The unit is to be connected to a 19" rack.

Mount the unit in the rack using the correct number of screws.

Do not block any ventilation openings.

Install in accordance with the manufacturer's instructions.

Always allow free air flow around the unit for cooling.

Ensure that no strain is placed on any cables connected to this apparatus. Ensure that all such cables are not placed where they can be stepped on, pulled or tripped over.

Power safety: This product satisfies FCC regulations when high quality shielded cables are used to connect with other equipment. Failure to use high quality shielded cables or to follow the installation instructions may cause electromagnetic interference with appliances such as radios and televisions and will void your FCC authorisation to use this product.

This equipment is supplied with mains lead however if you wish to use a mains cables of your choice refer to the following information:

Refer to the rating label on rear of the unit and always use a suitable mains cord.

The unit should ALWAYS be earthed.

Please use a compliant 60320 C13 TYPE SOCKET. When connecting to supply outlets ensure that appropriate sized conductors and plugs are used to suit local electrical requirements.

Maximum cord length should be 4.5m(15').

The cord should bear the approval mark of the country in which it is to be used.

Additionally: The appliance coupler is used as the disconnect device, ensure that it is correctly fitted to the wall outlet.

Connect directly to an AC power source that contains a protective earthing (PE) conductor.

ATTENTION! This product must always be earthed.

CAUTION! No user-serviceable parts inside. In the event of damage to the unit contact Solid State Logic. Service or repair must be done by qualified service personnel only.

This product complies with the following Canadian ICES-003.

Cet appareil numérique de la classe B est conforme à la norme NMB-003 du Canada.

The unit is to be connected to a 19" rack.

Mount the unit in the rack using the correct number of screws.

Do not block any ventilation openings.

Install in accordance with the manufacturer's instructions.

Always allow free air flow around the unit for cooling.

Ensure that no strain is placed on any cables connected to this apparatus. Ensure that all such cables are not placed where they can be stepped on, pulled or tripped over.

Power safety: This product satisfies FCC regulations when high quality shielded cables are used to connect with other equipment. Failure to use high quality shielded cables or to follow the installation instructions may cause electromagnetic interference with appliances such as radios and televisions and will void your FCC authorisation to use this product.

This equipment is supplied with mains lead however if you wish to use a mains cables of your choice refer to the following information:

Refer to the rating label on rear of the unit and always use a suitable mains cord.

The unit should ALWAYS be earthed.

Please use a compliant 60320 C13 TYPE SOCKET. When connecting to supply outlets ensure that appropriate sized conductors and plugs are used to suit local electrical requirements.

Maximum cord length should be 4.5m(15').

The cord should bear the approval mark of the country in which it is to be used.

Additionally: The appliance coupler is used as the disconnect device, ensure that it is correctly fitted to the wall outlet.


Connect directly to an AC power source that contains a protective earthing (PE) conductor.

ATTENTION! This product must always be earthed.

CAUTION! No user-serviceable parts inside. In the event of damage to the unit contact Solid State Logic. Service or repair must be done by qualified service personnel only.

</

For more information please visit
www.solidstateologic.com



Sales & Support

International Headquarters
Solid State Logic, 25 Spring Hill Road, Begbroke, Oxford, England, OX5 1RU
+44 (0)1865 842 300

Please recycle all packaging



04 PE-LD
21 PAP
22 PAP



Product Recycling Info



82BF7EX1A

Dette produkt er i overensstemmelse med følgende EU-harmoniseringsdirektiv:
EU's lavspændingsdirektiv (LVD) 2014/35/EU, EU's direktiv om elektronisk kompatibilitet (EMC) 2014/30/EU.

Kravene til miljøvenlig design af energierelaterede produkter (ERP) 2009/125/EF.

Directive om begrænsning af anvendelsen af visse farlige stoffer i elektrisk og elektronisk udstyr 2011/65/EU.

Se alle valgt tojejhæt, vaade jærmist teave:

Vaade seadme tagaküllə elevat andmesildi ja kasutage al Seade peaks ALATI olemä maandaud.

Palun kasutage nõuetekkuse vallast 60320 C13 TÜÜPI PISTIKUPES.

Toitepistikuteja ühendamisele veenduge, et kasutatakse sobiva suurega juhtmed ja pistikuid, mis vastavad kohalikele elek-

troniikale.

Juhitme maksimalne pikkus peaks olema 4,5m.

MHN rõõtuks peatatakse autun mõõdus, siis allalaag' endéhetas

ja pidevataks.

Juhitmele polemä tõlgitakse ümber.

Lihtsustatud.

Kravene til miljøvenlig design af energierelaterede produkter (ERP) 2009/125/EF.

Directive om begrænsning af anvendelsen af visse farlige stoffer i elektrisk og elektronisk udstyr 2011/65/EU.

Se alle valgt tojejhæt, vaade jærmist teave:

Vaade seadme tagaküllə elevat andmesildi ja kasutage al Seade peaks ALATI olemä maandaud.

Palun kasutage nõuetekkuse vallast 60320 C13 TÜÜPI PISTIKUPES.

Toitepistikuteja ühendamisele veenduge, et kasutatakse sobiva suurega juhtmed ja pistikuid, mis vastavad kohalikele elek-

troniikale.

Juhitme maksimalne pikkus peaks olema 4,5m.

MHN rõõtuks peatatakse autun mõõdus, siis allalaag' endéhetas

ja pidevataks.

Juhitmele polemä tõlgitakse ümber.

Lihtsustatud.

Kravene til miljøvenlig design af energierelaterede produkter (ERP) 2009/125/EF.

Directive om begrænsning af anvendelsen af visse farlige stoffer i elektrisk og elektronisk udstyr 2011/65/EU.

Se alle valgt tojejhæt, vaade jærmist teave:

Vaade seadme tagaküllə elevat andmesildi ja kasutage al Seade peaks ALATI olemä maandaud.

Palun kasutage nõuetekkuse vallast 60320 C13 TÜÜPI PISTIKUPES.

Toitepistikuteja ühendamisele veenduge, et kasutatakse sobiva suurega juhtmed ja pistikuid, mis vastavad kohalikele elek-

troniikale.

Juhitme maksimalne pikkus peaks olema 4,5m.

MHN rõõtuks peatatakse autun mõõdus, siis allalaag' endéhetas

ja pidevataks.

Juhitmele polemä tõlgitakse ümber.

Lihtsustatud.

RU

SSL 18 - Важная информация по безопасности**Общая безопасность**

Пожалуйста, прочитайте и сохраните этот документ и придерживайтесь всех предупреждений и инструкций. Это электрооборудование не должно подвергаться воздействию пыли, воды или других жидкостей. Чистите только сухой тканью или продуктами, совместимыми с электрическими устройствами, и никогда, когда устройство включено. Не работайте вблизи любых источников тепла, под прямыми солнечными лучами или вблизи открытого пламени.

Не размещайте тяжелые предметы на устройстве.

Используйте только надежное оборудование/аксессуары, рекомендованные производителем.

Отключите этот аппарат во время грозы или при неиспользовании в течение длительных периодов времени.

Не монтируйте устройство, изменения могут повлиять на производительность, безопасность и / или международные стандарты соответствия.

Устройство может обслуживаться только квалифицированным персоналом – обратитесь за немедленным обслуживанием, если консоль подверглась воздействию воды или если она перестает нормально работать.

SSL не несет ответственности за ущерб, причиненный техническим обслуживанием, ремонтом или модификации неавторизованным персоналом.

При использовании этого устройства либо закрепите его в стандартной 19-дюймовой стойке, либо поместите на безопасную ровную поверхность.

Если устройство монтируется в стойке, установите все винты. Рекомендуется использовать болты для стеллажей.

Не блокируйте вентиляционные отверстия. Установка в соответствии с инструкциями производителя.

Всегда допускайте свободный поток воздуха вокруг устройства для охлаждения.

Убедитесь, что на кабели, подключенные к этому устройству, не напрягаются. Убедитесь, что все такие кабели не размещены там, где их можно наступить, потянуть или споткнуться.

Энергетическая безопасность

Это оборудование поставляется с сетевым проводом, однако, если вы хотите использовать сетевые кабели по вашему выбору, обратитесь к следующей информации:

Обратитесь к маркировке на задней панели устройства и всегда используйте подходящий сетевой шнур.

Устройство CE/GCFD должно быть заземленным.

Пожалуйста, используйте совместимый разъем 60320 C13 TYPE. При подключении к розеткам питания убедитесь, что проводники и вилка соответствующего размера используются в соответствии с местными электрическими требованиями.

Максимальная длина шнура должна составлять 4,5 м.

Шнур должен иметь знак официального утверждения страны, в которой он будет использоваться.

Дополнительно: Соединитель прибора используется в качестве разъединяющего устройства, убедитесь, что он подключен к беспрепятственной настенной розетке.

Подключайтесь только к источнику питания переменного тока, содержащему проводник защитного заземления (P).

Подключите блоки только к однозначным источникам питания с нейтральным проводником на заземляющем потенциале.

Внимание! Это оборудование всегда должно быть заземленным.

ОСТОРОЖНОСТИ Внутри нее не обслуживаемых пользователем деталей. В случае повреждения блока или блока питания обращайтесь в Solid State Logic. Обслуживание или ремонт должны выполняться только квалифицированным сервисным персоналом.

Электромагнитная совместимость

EN 55032:2015, класс 2. EN EMI 55035:2017.

ПРЕДУПРЕЖДЕНИЕ: Аудиопорты ввода/вывода являются экранированными кабельными портами, и любые соединения с ними должны быть выполнены с использованием кабеля



Задний щиток

Логотип: Solid State Logic

</